

Model # 11050N

AUTORANGING MULTIMETER

Compact multimeter with rugged double molded housing and CAT III safety rating provides many plus features including Max/Min/Record and 6,000-count backlit display with bar-graph.



EASY TO READ DISPLAY
Backlit, 6,000-count display with bargraph

MULTI FUNCTION
Capacitance, Frequency, Duty Cycle, and Temperature functions

NON-CONTACT VOLTAGE TESTER
Built-in AC NCV Detector

MAX/MIN/RECORD
Captures voltage fluctuations

12 FUNCTIONS

- AC Voltage
- DC Voltage
- Non-Contact AC Voltage
- AC Current
- DC Current
- Resistance
- Capacitance
- Frequency
- Duty Cycle
- Temperature
- Continuity
- Diode Test



southwiretools.com

southwiretools.com

BUILT FOR DURABILITY. BUILT FOR RELIABILITY.
BUILT FOR WORK.



Southwire™

FEATURES

- High resolution 6,000-count display
- Capacitance, Frequency, Duty Cycle, and Temperature functions
- Built-in non-contact AC voltage detector
- CAT III 600 V, ETL certified

INCLUDES

- 11050N Multimeter
- Test leads
- Type K temperature probe with banana plug adapter
- 9 volt battery

SPECIFICATIONS

AUTO-RANGE MULTIMETER (11050N)			
	Range	Max. Resolution	Basic Accuracy (% of reading)
AC Voltage:	600V	1.0mV	±1.5%
DC Voltage:	600V	0.1mV	±0.5%
NCV (non-contact AC Voltage)	100 to 600V	-	-
AC Current:	10A	1.0mA	±3.0%
DC Current:	10A	1.0mA	±2.5%
Resistance:	60MΩ	0.1Ω	±1.2%
Capacitance:	1000μF	10pF	±3.0%
Frequency:	10MHz	0.001Hz	±1.2%
Duty Cycle:	99.9%	0.1%	±1.2%
Temperature:	-4 to 1400°F -20 to 760°C	1°F 1°C	±3.0%
Continuity:	Audible threshold: Approximately 30Ω		
Diode Test:	Yes		
Dimensions:	5.91 x 2.76 x 1.89 in.		
Weight:	520g		



Southwire Company
One Southwire Drive
Carrollton, GA 30119



Southwire™



Customer Service: 1-855-SWTOOLS (855-798-6657)

Scan code to see more
Southwire Tools
southwiretools.com